

SUBSTITUTE SPECIFICATION

TITLE: METHOD OF PREVENTING RECORDING ON A DISC-LIKE
RECORDING MEDIUM OF THE OPTICALLY REWRITABLE TYPE

INVENTOR(S): JAKOB G. NIJBOER ET AL.

SERIAL NO.: 10/761,025

ATTY. DOCKET NO.: PHN 17,787A

METHOD OF PREVENTING RECORDING ON A DISC-LIKE
RECORDING MEDIUM OF THE OPTICALLY REWRITABLE TYPE

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This is a continuation of U.S. Patent Application Serial
No. 09/685,553, filed October 10, 2000, now U.S. Patent 6,704,263.

BACKGROUND OF THE INVENTION

Field Of The Invention

[0002] The invention relates to a method of preventing recording
on a disc-like recording medium of the optically rewritable type,
the method comprising applying a pre-groove on the disc-like
recording medium adapted to write data therein in accordance with a
first write strategy, reserving a program calibration area (PCA)
for optimum power control (OPC) and/or a program memory area (PMA)
for temporarily storing a table of content (TOC) on said disc-like
recording medium.

[0003] The invention further relates to a recording apparatus
adapted for recording digital information signals on a disc-like
recording medium of the optically rewritable type, said apparatus
comprising input means for receiving digital information signals,
encoding means for coding the received digital information signals
for recording on the disc-like recording medium, writing means for
writing optically detectable marks representing the encoded
information signals on the disc-like recording medium in accordance

with a first write strategy, address determining means for locating, on the disc-like recording medium, a program calibration area (PCA) to be used for a optimum power control (OPC) procedure, and/or a program memory area (PMA) to be used for temporarily
5 storing a table of content (TOC).

[0004] The invention also relates to a disc-like recording medium of the optically rewritable type having a pre-groove adapted to record data therein in accordance with a first write strategy, a Program Calibration Area (PCA) adapted to be used in a Optimum
10 Power Control (OPC) procedure and/or, a Program Memory Area (PMA) adapted to temporarily store a table of content (TOC).

Description Of The Related Art

[0005] A disc-like recording medium of the optically type is
15 disclosed, for instance, in European Patent No. 390 268 (PHN13148), which is incorporated herein by reference. Such a disc which allows recording apart from playback may be referred to as a CD-Recordable (CD-R), a CD-Erasable (CD-E) or a CD-Rewritable (CD-RW).

[0006] As the name implies, CD-RW is a media and recording
20 system that allows the user to erase previously recorded information and then to record new information in its place, making short-term storage feasible on CD media. This is accomplished by means of a new CD-RW media using "phase change" technology that allows a recording laser beam to change the media material from
25 amorphous to crystalline by means of a shift in power.

[0007] The first generation of CD-RW discs are designed for speed applications covering a range of 1 times - 4 times the nominal speed of a conventional CD-ROM disc, being approximately 150 kbs. The next generation CD-RW discs however will be designed for high-speed applications ranging from 4 times - 10 times this nominal speed. Because of the typical behavior of phase change materials, these discs need a new write strategy, which is not suited for recording at lower speeds. Furthermore, the existing write strategies defined for 1X, 2X and 4X recording speed, do not work on these new discs.

[0008] Some of the existing CD-RW recorders, designated to operate with the lower speed ranges, are recognizing the new high-speed discs and reject them. But others will accept these discs and make recordings on them according to one of the existing write strategies, for instance default at 2X speed. These recordings will result in unreadable signals, thereby destroying previously recorded information.

SUMMARY OF THE INVENTION

[0009] It is an object of the invention to obviate the above-mentioned disadvantages. According to one aspect, a method according to the invention is characterized by making one or both of said areas untraceable for recording devices adapted to write data on a disc-like recording medium in accordance with a second, different write strategy.

[0010] As both areas are needed by a recorder, hiding these areas for existing recorders, designed to operate with low speeds, will result in rejecting of the disc.

[0011] In a method comprising applying absolute time reference
5 (ATIP) information in the pre-groove on the disc-like recording medium, in which start locations of said areas are being determined by a fixed time offset relative to a subsequent Lead-in area, an advantageous embodiment thereof is characterized by introducing an ATIP time code jump to ATIP time codes before the start of the
10 Lead-in area. The Pre-Groove of a CD-RW disc contains an Absolute Time Reference in the Pre-Groove. As the locations of the PCA and PMA areas are determined by a fixed offset relative to the Start time of the Lead-in areas, these areas are made untraceable.

[0012] Further advantageous embodiments of a method according to
15 the invention are disclosed in the description, as well as embodiments of a disc-like recording medium and recording apparatus according to the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

20 [0013] These and further aspects and advantages of the invention will be discussed in more detail hereinafter with reference to the disclosure of preferred embodiments, and in particular, with reference to the drawings, in which:

[0014] Fig. 1 is a chart showing an existing ATIP versus disc
25 diameter;

[0015] Fig. 2 is a chart showing a modified ATIP versus disc diameter, modified according to a first embodiment of the invention;

[0016] Fig. 3 is a chart showing the detailed organization of the PCA, PMA and Lead-in area of Fig.2, modified according to a second embodiment of the invention;

[0017] Fig. 4 is a chart showing a modified ATIP versus disc diameter, modified according to a third, preferred embodiment of the invention; and

10 [0018] Fig. 5 shows a schematic block diagram of a recording apparatus according to an embodiment of the invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0019] In a CD-RW, there are two areas preceding the Lead-in area that are reserved for use by the recorder. The Power Calibration Area (PCA) is intended for making test recordings to determine the optimal write power for the actual disc. Every time a disc is inserted into a CD-RW drive, the laser is fired at the surface of the PCA to judge the optimum power setting for burning the CD. Various things can influence this optimum setting - the recording speed, humidity, ambient temperature and the type of disc being used. The Program Memory Area (PMA) is intended to store a temporary Table of Content (TOC). A TOC contains track numbers and their start and stop times (for music), or sector address for the start of data files on a data CD.

[0020] The Information Area, i.e., the area of the disc which contains data, is divided into three areas, notably, the Lead-in area, the Program Area and the Lead-out area. The Lead-in area contains digital silence in the main channel plus the Table of Contents (TOC) in the subcode Q-channel. The Lead-in area allows the laser pickup head to follow the pits and synchronize to the audio or computer data before the start of the program area. The Program Area contains up to about 76 minutes of data divided into 99 tracks maximum. The Lead-out area contains digital silence or zero data. This defines the end of the CD program area.

[0021] Both PCA and PMA areas are needed by the recorder. As such, if they can be hidden from existing recorders for low application speeds, these recorders cannot perform an Optimum Power Control (OPC) procedure and cannot read the temporary TOC. As a result, these recorders will reject the disc.

[0022] The locations of the PCA and PMA areas are determined by a fixed time offset relative to the Start time of the Lead-in area, as illustrated in Fig. 1

[0023] On the new generation of high speed discs, the PCA and PMA could be made untraceable, according to a first embodiment of the invention, for existing drives by introducing an ATIP time code jump of, for instance, 1 minute just before the Start time of the Lead-in area. In other words, all ATIP time codes up to the Start time of the Lead-in area are reduced by one minute, as illustrated in Fig. 2.

[0024] Existing drives cannot distinguish between old and new discs and, therefore, will search for an ATIP time code (t3-00:35:65) or (t3-00:13:25) to find the PCA or the PMA, respectively, which they find on old discs, but never find on new
5 discs. As a result they will reject the new discs.

[0025] New drives or upgraded drives adapted to operate with high speed discs at higher speed applications, can recognize the new discs and know about the existence of the ATIP time code jump, and will search for (t3-01:00:00 - 00:35:65) or (t3-01:00:00 -
10 00:13:25) to find the PCA or the PMA, respectively, on new discs.

[0026] However, because some recorders are using the PMA also for access during playback, an advantageous second embodiment leaves the PMA untouched. In order to achieve this, the ATIP Time Code jump is chosen as illustrated with reference to Fig. 3. To
15 have some buffer area before the PMA, which might be useful for good access control, the time code jump could possibly be better located just after the last used frame of the count area in the PCA as illustrated in FIG. 3. Herein, $T_{SL} = t_3$ = Start time Lead-in.

[0027] Fig 4 shows a preferred third embodiment according to the
20 invention. As shown in Fig. 4, the power calibration area PCA is divided into two areas. A first area is a Test Area, in which tests can be performed to obtain correct reading power for a disc. A second area is a Count Area, where it can be read which part of the Test Area can be used. Both areas of the PCA are divided into
25 partitions, which must be used in sequential order, starting from

partition number one. The PCA can be used many times, i.e., once all partitions have been used, the total PCA must be erased, after which it is available for the next sequence of power calibration procedures. The ATIP jump location is, with respect to the
5 embodiments shown in Fig. 2 and Fig. 3, shifted into the buffer area between the PCA Test Area and the PCA Count Area. This results in a distance between the ATIP jump and the PMA area of 2 minutes. This gives the advantage of more space for drives to access the PMA. As some drives may employ the Program Memory Area (PMA), the
10 available free space or buffer area may be insufficient for the use as explained with reference to Fig. 2 and Fig. 3. It is noted that drives expect PCA Test partitions from 96:51:30 to 97:11:29.

[0028] Next an embodiment of a recording apparatus according to the invention will be described, with reference to Fig. 5. The
15 recording apparatus 1 comprises recording medium receiving means 2 for receiving a removable recording medium 3. The recording medium 3 may be a disc of the optically rewritable type, such as CD-RW, DVD-RAM or DVD-RW. The recording medium 3 is rotationally driven by rotation means 4. An optical pick-up unit 5, movable in a radial
20 direction of the recording medium 3, writes optically detectable marks along a spiral track 8 on the recording medium 3 employing a light beam 6. To this end, the recording medium 3 is provided with a suitable phase-change material which has different optical properties in crystalline or amorphous states. Heating with the
25 light beam 6 may induce these states. The light beam 6 is modulated

by recording means 9 according to digital information signals to be recorded. These digital information signals have been suitable encoded by encoding means 10, employing EFM modulation and CIRC error encoding, as prescribed by the CD-standards. Input means 11, which may comprise A/D conversion means and/or special interface circuitry, may receive analog and/or digital information signals.

[0029] Alternatively, recorded digital information signals on the recording medium 3, may be read via the same optical pick-up unit 5, by suitable reading means 13. The reading means 13 is connected to decoding means 14 for performing EFM decoding and CIRC error correction processing. The decoded and corrected signals are outputted, via outputting means 15, which may comprise D/A means and/or suitable interface circuitry, digital and/or analog information signals.

[0030] In addition, address finding means 12 is provided to determine address information present on the recording medium 3. Such address information, for example, in the form of absolute time codes, may be recorded in the track 8 by means of a pre-formed track modulation as disclosed in European Patent No. 390 268 (PHN 13148). Such a track is described in more detail in the Dutch Patent Application NL-A-8800152, corresponding to U.S. Patent 4,999,825 (PHN 12399). The address finding means 12 derives an address signal from the signal components in the detection signals which are caused by the pre-formed track modulation. The address signal is supplied to the controlling unit 16.

[0031] All units are controlled by the controlling unit 16. The controlling unit 16 may comprise a processing unit which operates according to a specific program loaded in memory means, in order to perform the method according to the invention.

5 [0032] Specifically, the controlling unit 16 comprises information relating to the time jump in the Absolute Time Reference (ATIP) as may be present in the recording medium 3, as described before. This enables the recording apparatus 1 to locate the previously-mentioned areas on a recording medium 3 to be used
10 for an Optimum Power Control (OPC) procedure and/or recording of a temporary table of content (TOC).

[0033] Although the invention has been described with reference to a preferred embodiment thereof, it is to be understood that these are not limitative example. Thus, various modifications
15 thereof may become apparent to those skilled in the art, without departing from the scope of the invention, as defined by the claims. The invention may be implemented by means of both hardware and software, and that several "means" may be represented by the same item of hardware. Further, the invention lies in each and
20 every novel feature or combination of features. It is also remarked that the word "comprising" does not exclude the presence of other elements or steps than those listed in a claim. Any reference signs do not limit the scope of the claims.